



PRODUCT MANUAL

VIPER[®] HS[™]

SFP RIFLESCOPES

SPECIFICATIONS

CONFIGURATION	2.5-10x44	4-16x44	4-16x50
SKU	VHS-4303	VHS-4305	VHS-4307
RETICLE	Dead-Hold [®] BDC MOA		
FOCAL PLANE	Second Focal Plane (SFP)		
EYE RELIEF	4.0" (101.6mm)		
LINEAR FIELD OF VIEW (@100 YDS.)	47.0' - 10.9'	27.4' - 7.4'	
TURRET STYLE	Elevation - Capped Windage - Capped		
TUBE SIZE	30mm		
ADJUSTMENT GRADUATION	1/4 MOA		
TRAVEL PER ROTATION	12 MOA		
MAX ELEVATION ADJUSTMENT	86 MOA	50 MOA	50 MOA
MAX WINDAGE ADJUSTMENT	86 MOA	50 MOA	50 MOA
PARALLAX SETTING	100 yds.	50 yds.	- ∞
LENGTH	12.0"	13.4"	13.6"
WEIGHT	17.3 oz.	19.2 oz.	20.4 oz.

2.5-10x44



4-16x44



4-16x50



DIMENSIONS	2.5-10x44	4-16x44	4-16x50
OVERALL LENGTH	L1 12.0"	L1 13.4"	L1 13.6"
FRONT MOUNTING SURFACE	L2	L2	L2 2.1"
REAR MOUNTING SURFACE	L3	L3	L3 2.2"
OVERALL MOUNTING SURFACE	L4 5.6"	L4 5.6"	L4 5.7"
OBJECTIVE LENGTH	L5 2.9"	L5 4.2"	L5 4.3"
EYEPiece LENGTH	L6	L6 3.6"	L6 3.6"
OUTSIDE DIAMETER OBJECTIVE	H1 2.0"	H1 2.0"	H1 2.3"
OUTSIDE DIAMETER EYEPiece	H2	H2 1.7"	H2 1.7"
MAGNIFICATION RING OUTSIDE DIAMETER	H3	H3 1.8"	H3 1.8"
TURRET SADDLE DEPTH	H4	H4 0.1"	H4 0.1"

VIPER® HS™ RIFlescOPES

Viper® HS™ riflescopes offer hunters and shooters an array of features sure to be well received. The advanced optical system, highlighted with a 4x zoom range, provides magnification versatility. A forgiving eye box with increased eye relief gets shooters on target quickly and easily. Built on an ultra-strong 30mm one-piece machined aluminum tube, the Viper® HS™ delivers increased windage and elevation travel for optimal adjustment.



Images are for representation only. Product may vary slightly from what is shown.

INITIAL SET UP

Reticle Focal Plane (Second Focal Plane vs First Focal Plane)

All riflescope reticles can be termed either first focal plane (FFP) or second focal plane (SFP), with respect to the reticle's internal location within the erector system. An SFP reticle is visually consistent in size and weight across the magnification range; however, the subtension values are only accurate on one magnification, typically the highest. In contrast, an FFP reticle will scale with magnification, and their subtensions used for ranging, holdovers, and wind corrections will remain constant. The reticle size will appear larger at higher magnifications, and smaller at low magnification.

Second Focal Plane Reticle

The Viper® HS™ riflescopes feature a second focal plane (SFP) reticle. SFP reticles are located within the riflescope near the magnification ring. This style of reticle will appear consistent throughout the entire magnification range.



Note: The Viper® HS™ riflescopes' reticles are calibrated to the highest magnification.

Ocular Focus – Fast-Focus Eyepiece

The ocular focus is typically a one-time adjustment used to focus the reticle for maximum sharpness.

This adjustment is slightly different for every shooter.

A clearly focused reticle is a critical component for accurate shooting. When setting up a scope, this should be the first adjustment you make and should only need to be changed from user to user, or if your eyesight changes over time.



Once this adjustment is complete, it will not be necessary to refocus every time you use the rifle scope. However, because your eyesight may change over time, you should recheck this adjustment periodically.

Parallax

Parallax results when the target image is not on the same optical plane as the reticle within the scope. This can cause an apparent movement of the reticle in relation to the target if the shooter's eye is off-axis behind the optic.

Ocular Focus – Fast-Focus Eyepiece Adjustment

The Viper® HS™ riflescopes use a Fast-Focus Eyepiece designed to easily adjust the focus on the rifle scope's reticle.

WARNING: Looking directly at the sun through a rifle scope, or any optical instrument, can cause severe and permanent damage to your eyesight.

Adjusting the reticle focus to your eye:

1. Turn the Magnification Adjustment Ring to the highest power and the Parallax Adjustment Knob (on applicable models) to infinity. Looking through the optic, turn the Fast-Focus Eyepiece counterclockwise until the reticle is slightly blurry.
2. While looking at a white wall or a clear blue sky, taking short glances through the optic, turn the Fast-Focus Eyepiece clockwise until the reticle is clear and crisp as soon as you look through the optic. This may take several attempts.

Note: You do not want your eye to focus to the reticle, rather you want the reticle in focus to your eye instantly when looking through the optic. Looking away and letting your eyes refocus is important in getting the Fast-Focus Eyepiece set correctly.

Fixed Parallax

The Viper® HS™ 2.5-10x44 SFP rifle scope comes equipped with a fixed parallax setting at 100 yards. There is no adjustment on this model.

With a fixed 100 yard parallax, the shooter may experience small amounts of parallax error inside and outside of 100 yards, or if the shooter is off-axis behind the optic. If the shooter is perfectly aligned behind the optic, or at 100 yards, there should be no parallax error.

Adjustable Parallax

The Viper[®] HS[™] 4-16x riflescopes come equipped with a Parallax Adjustment Knob located on the left-hand side of the turret saddle. When the parallax is properly adjusted, the shooter should experience no parallax error.



Parallax Adjustment Knob

Dial the Parallax Adjustment Knob until the target image is as sharp as possible. The yardage numbers on the knob should be used as general reference points only. Check for parallax error by moving your head up, down, left, and right without influencing the gun. The parallax is correct if there is no apparent shift between the reticle and the target image. If you notice any shift, adjust the focus knob slightly until all shift is eliminated.

Note: If the reticle and the image are not both simultaneously in focus, readjust your Fast-Focus Eyepiece. See Ocular Focus – Fast-Focus Eyepiece section.

Magnification Adjustment

The Magnification Adjustment Ring is used to change the rifle scope's "power." The Viper[®] HS[™] riflescopes are variable powered optics with a 4x optical design.

To adjust your optic's magnification, rotate the Magnification Adjustment Ring clockwise, or counterclockwise, to increase or decrease the magnification to your desired level.




TURRETS

The Viper[®] HS[™] riflescopes are offered in Minute of Angle (MOA). The Viper[®] HS[™] riflescopes have matching reticle/turret configuration.

Minute of Angle (MOA) Adjustment


Minute of Angle is an angular unit of measurement commonly found in riflescopes. It is used to measure bullet drop, wind holdovers, and for measuring targets. Both the reticle and turrets will be laid out in specific MOA values. 1 MOA equates to 1.047" at 100 yards, 2.09" at 200 yards, 3.14" at 300 yards, etc. Being an angular unit of measurement, the value of 1 MOA will increase/decrease proportionally as you increase/decrease the distance you are shooting. For this reason, think about all of your adjustments in MOA, rather than a linear unit such as inches. If your turret, reticle, and drop chart are all laid out in MOA, adjusting your scope for bullet drop or windage corrections is extremely easy.

1 MOA = 1.047" per 100 yards.



Elevation and Windage Turrets

Use turrets to adjust the bullet's point of impact. The Viper® HS™ riflescopes use a 1/4 MOA turret adjustment on the Elevation and Windage Turrets. Each click will move the bullet's point of impact roughly .25" at 100 yards for MOA. The turret on the top of the riflescope is the Elevation Turret, which is used to adjust the bullet's point of impact up and down. The turret on the right-hand side of the riflescope is the Windage Turret and is used to adjust the bullet's point of impact left and right.



Capped Turrets

The Viper® HS™ riflescopes come equipped with a capped Elevation and Windage Turrets. This protects the turrets from accidental adjustment while out in the field, in transit, or in storage. You will need to remove the caps prior to making any adjustments on the turrets.

Note: The scope is still waterproof with the caps removed.

Adjusting Capped Turrets:

1. Remove the turret caps by spinning them counterclockwise.
2. Following the directional arrows, turn the dial in the direction you wish the bullet's point of impact to change. (If you hit high, dial down. If you hit low, dial up. If you hit right, dial left. If you hit left, dial right.)
3. When finished adjusting, replace the turret caps.

Note: The reticle will move in the opposite direction of the turret dials. When you dial up, the reticle will move down, forcing you to aim higher, changing your point of impact upward.

RIFLESCOPE MOUNTING

To get the best performance from your riflescope, proper mounting is essential. Although not difficult, the correct steps must be followed. If you are unsure of your abilities, use the services of a qualified gunsmith.

Please take note of the instructions on the following pages. For the proper scope mounting procedure go to VortexOptics.com/vortex-nation-videos for a video tutorial.

Riflescope Mounting Checklist

- Gun vise or a solid platform for your rifle
- Scope rings
- Torque wrench
- Reticle leveling tool(s) (such as feeler gauges or bubble levels and a plumb bob)

Recommendation: Pick up the Vortex® Torque Wrench Mounting Kit, which comes with the complete set of bits needed to install Vortex® scopes and rings.



Rings and Bases

The Viper® HS™ riflescopes feature a 30mm main tube. Be sure to select a base and matching rings appropriate for your riflescope's mount according to manufacturer's instructions.

Tip: Selecting the proper ring height to provide appropriate clearance between the riflescope and any part of the rifle is paramount. The proper height will also allow for a comfortable head position and aid in establishing a solid and consistent shooting position. A ring's height will not have an adverse effect on accuracy and overall range or performance.

Eye Relief and Reticle Adjustment

After installing the bottom ring halves on the mounting base, place the riflescope on the bottom ring halves and loosely install the upper ring halves. Before tightening the scope ring screws, adjust for maximum eye relief to avoid injury.

1. Set the riflescope to its highest magnification.
2. Move the riflescope fore and aft in the rings until you achieve a full, unobstructed sight picture.
3. Without disturbing the fore-aft placement, rotate the riflescope until the reticle is level. Use a leveling tool(s) such as feeler gauges or bubble levels and a plumb bob to aid in this process.
4. After leveling the reticle, tighten and torque the ring screws down per manufacturer's instructions. Use caution and do not over-tighten ring screws.

Note: We typically suggest 15-18 in.-lbs of torque on the ring screws. If the mounting manufacturer suggests more or less, contact the Vortex[®] Technical Department for best instructions. For base clamp screws on the rings/mounts, reference the ring manufacturer's specifications. We do not recommend liquid thread-locking compound on the ring screws.

If you have questions about a specific setup, please call our Technical Department at:

1-800-4VORTEX (1-800-486-7839) Ext 5

SIGHTING IN YOUR RIFESCOPE

Bore Sighting

Initial bore sighting of the riflescope will save time and money at the range by roughly aligning the scope to the rifle. This can be done several ways, either by using a mechanical or laser bore sighter according to the manufacturer's instructions, or by removing the bolt and sighting through the barrel.



To Visually Bore Sight a Rifle

1. Place the rifle on a solid rest and remove the bolt.
2. Sight through the bore at a target approximately 100 yards away.

Note: It will help to have larger, high contrast target to focus on as it can be difficult to pick up smaller targets through the rifle's bore.

3. Move the rifle and rest until the target is visually centered inside the barrel.
4. With the target centered in the bore, make the necessary windage and elevation adjustments until the reticle is also centered on the target. You may notice the reticle travel in the opposite direction as listed on the turrets. This is completely normal.

Final Range Sight-In

After the riflescope has been bore sighted, final sight-in should be done at the range using the exact ammunition you expect to use while hunting or shooting competitively. Sight-in and zero the riflescope at the preferred distance. 50 to 200 yards are the most common zero distances.

1. Following all safe shooting practices, fire a three-shot group as precisely as possible to determine an average point of impact to correct from. This will also help you establish the accuracy potential of the weapon system.
2. Adjust the turrets to correct for any offset in your point of impact. Be sure to read page 8 prior to adjusting.
3. Fire another three-shot group to establish another average point of impact. This procedure may be repeated as many times as necessary until your point of impact and your point of aim are in the same place, and you have achieved a perfect zero.

Note: Vortex® does not recommend the use of a weighted gun vise, as it can put extreme stress on the gun, stock, scope, and mounts. It is best practice to use a combination of sandbags or a blood and sandbags. Letting your weapon recoil naturally also provides consistency from shot to shot.

Reindexing the Elevation and Windage Turrets

After the rifle and scope have been zeroed in, the elevation and windage turrets should be reindexed to their zero indicators. This will allow you to accurately keep track of elevation or windage corrections dialed on the turrets in the field, and quickly return to an original zero-point setting.

To Reindex Capped Turrets

1. Remove the outer cap and pull the adjustment dial outward against the spring tension until it stops.
2. With the dial pulled fully outwards, rotate the dial to reposition the zero mark on the index line.
3. Release the dial, allowing it to return to the normal inward position.
4. Replace the turret cap.

MAINTENANCE

Cleaning

Your Vortex® riflescope requires very little routine maintenance other than periodically cleaning the exterior lenses. The scope's exterior may be cleaned by wiping with a soft cloth. When cleaning the lenses, be sure to use products that are specifically designed for use on coated optical lenses.

- Be sure to blow away any dust or grit on the lenses prior to wiping the surfaces.
- Using your breath, or a very small amount of water or pure alcohol, can help remove stubborn dried water spots.

Lubrication

All components of the riflescope are permanently lubricated, so no additional lubricant should be applied.

Note: Other than removing the turret caps, do not attempt to disassemble any components of the riflescope. Disassembling of riflescope may void warranty.

Storage

If possible, avoid storing your scope in direct sunlight or any very hot location for long periods of time.

TROUBLESHOOTING

Please consult the following list prior to returning a riflescope for service. Many times, a problem thought to be with the scope is a mounting issue. Be sure the correct rings and bases are being used and that they are properly torqued to the rifle. Be sure there is no free play in the scope, base, or rings.

Common Issues

Point of Impact is Inconsistent or Changes Drastically After Turret Adjustment.

- Verify that the ring screws are not over-torqued. Ring screws should only be torqued to Vortex® recommendations, and no thread-locking compound or lubricants should be applied. Over-torquing ring screws will cause excess pressure on the tube, which may cause problems when making turret and parallax adjustments.

- Remove the scope from the rings and visually check the scope tube for slide marks, and/or indentations from over-torqued, or out-of-spec rings.

- Ensure the rifle's action screws are tightened to the rifle manufacturer's specification.
- Be sure that the base is tightened using thread-locking compound to the top of the rifle's receiver to manufacturer's specs.
- If using the scope on an AR-style rifle, ensure that the cantilever mount/rings are mounted only to the top of the receiver. The cantilever mount/rings need to be mounted to a single, solid surface. Make sure the forward connection of the cantilever mount, or ring, is not mounted to the fore-end of the rifle.
- Be sure the rifle barrel and action are clean and free of excessive oil, or copper and powder fouling.
- Some rifles and particular ammunition do not work well together. Try different ammunition and see if accuracy improves.

Insufficient Windage & Elevation Adjustment Range

- Be sure you have the proper base and rings for your rifle. If you need assistance, contact a local gunsmith or the Vortex® Technical Department.
- Once you have verified you have the correct base and mounts, and that you have been properly fitted for your gun, make sure you have followed the correct mounting procedure. See Riflescope Mounting Section on page 10 for this procedure.
- Insufficient windage or elevation adjustment range usually indicates problems with the mounting, base mount holes drilled in the rifle's receiver, or barrel/receiver misalignment.

Cannot Focus on the Reticle and Target

- Check and reset the ocular focus for the shooter's eye. See Riflescope Adjustment Section, Ocular Focus – Fast-Focus Eyepiece Adjustment on pages 5 and 6.

Reticle is Moving the Wrong Direction

- The reticle will always move opposite of the turrets. Markings on the turrets indicate point of impact change. If you dial down on the turret, the reticle will move upward, forcing you to move the gun down, to change your point of impact downward.

NOTICE**Virtual Patent Marking Notice by Vortex Optics**

This product may be protected by patents in the U.S. and elsewhere for Vortex Optics. <http://vtx.legal> website is provided to satisfy the virtual patent marking provisions of various jurisdictions including the virtual patent marking provisions of the America Invents Act and provide notice under 35 U.S.C. §287(a). Please visit <http://vtx.legal> to view list of products that may be covered by one or more U.S./Foreign patents or published patent applications.

**VIP WARRANTY[™]
OUR UNCONDITIONAL PROMISE TO YOU.**

We promise to repair or replace the product. Absolutely free.

- ▶ **Unlimited.**
- ▶ **Unconditional.**
- ▶ **Lifetime Warranty.**

You do not have to register, save the box, or a receipt for the Warranty to be honored.

Learn more at VortexOptics.com

service@VortexOptics.com • 1-800-4VORTEX

Note: The VIP Warranty[™] does not cover loss, theft, deliberate damage, or cosmetic damage not affecting product performance.

For the most up to date manual visit VortexOptics.com



M-00351-0

© 2023 Vortex Optics

® Registered Trademark and TM Trademark of Vortex Optics. Patent Pending