



RETICLE MANUAL

VMR-1

MOA RETICLE


SECOND FOCAL PLANE

VORTEX® VMR-1 MOA RETICLE


You have purchased a Vortex® rifle scope equipped with the VMR-1 reticle. Designed to maximize long distance shooting and ranging abilities, the VMR-1 MOA reticle can be used to effectively determine ranges, holdovers, windage corrections, and moving target leads.

MOA Subtensions

The VMR-1 reticle is based on minute of angle (MOA) subtensions. MOA measurements are based on degrees and minutes: 360 degrees in a circle, 60 minutes in a degree for a total of 21,600 minutes. These angular measurements are used to estimate range and correct for bullet trajectory drop in riflescopes. 1 MOA will correspond to 1.05 inches at a 100 yard distance, 2.1 inches at 200 yards, 3.15 inches at 300 yards, and so on.



VMR-1 MOA Reticle



Subtensions measured in MOA.

Reticle image shown for representation only.

Second Focal Plane Reticles

Second focal plane (SFP) reticles are located near the scope's eyepiece behind the image erecting and magnifying lenses. This style of reticle does not visually change in size when you change the magnification. The advantage of an SFP reticle is that it always maintains the same, ideally sized appearance. When shooting with this SFP scope, be aware that the listed reticle subdivisions used for estimating range, holdover, and wind drift correction are only correct at the highest magnification for all models.

Ranging


MOA measurements are very effective for ranging using a simple formula. To use this formula, the shooter needs to know the size of the target, or nearby object, in inches.

MOA Ranging Formula

$$\frac{\text{Target Size (Inches)} \times 95.5}{\text{Measured MOA}} = \text{Range (Yards)}$$

Using either the vertical or horizontal MOA scale, place the reticle on a target of known dimensions and read the number of MOA spanned. You will obtain maximum accuracy in ranging by calculating exact MOA measurements. MOA should be estimated in halves if possible.

Accurate measuring will depend on a very steady hold. The rifle should be solidly braced using a rest, bipod, or sling when measuring. Once you have an accurate MOA reading, use the formula to calculate the distance.




Ranging a target stand that is six feet (72 inches) tall at 8 MOA to get 860 yards.

$$\frac{72 \times 95.5}{8 \text{ MOA}} = 860 \text{ yds.}$$

Elevation Holdovers

Once you've calculated distance using the VMR-1 or a laser rangefinder, the VMR-1 can be used for rapid holdover correction of the bullet drop. Vortex Optics highly recommends shooters learn their bullet drop numbers and windage/lead corrections in MOA rather than inches or Milliradians (MRAD). Remember that 1 MOA will correspond to 1.05 inches at a 100 yard distance, 2.1 inches at 200 yards, 3.15 inches at 300 yards, and so on.

Since this VMR-1 reticle is marked in MOA, it is an easy job to quickly select the correct drop reference line once the shooter knows the bullet drops and windage/lead corrections in MOA. If the shooter prefers to dial the holdover for bullet drop using the elevation knob, knowing bullet drops in MOA will allow for much faster adjustments because the MOA can be quickly read on the elevation knob.



12 MOA reticle holdover correction for 600-yard shot. No wind.


Windage and Moving Targets

The VMR-1 reticle is highly effective when used for wind and moving target leads. Using the reticle for effective windage and moving leads requires a thorough knowledge of your cartridge's ballistic performance under varying conditions, and experience in reading wind strengths and target speeds. As in bullet drops, it is imperative the shooter learn their particular weapon's windage/moving target corrections in MOA rather than inches or MRAD. Always hold the reticle into the wind when correcting for wind drift.

When dialing elevation holdovers, the center horizontal crosshair will be used for windage or moving target leads. MOA marks on the horizontal and vertical crosshairs are graduated in 2 MOA increments.

Basic Windage Correction on Center Crosshair

When dialing elevation holdovers, the center horizontal crosshair will be used for windage or moving target leads. MOA marks on the horizontal crosshair are graduated in 2 MOA increments.




10 MOA reticle correction for 20 mph wind at 700 yards. Elevation is already dialed into turret.

Basic Moving Lead Correction

When estimating moving target leads, use the MOA marks on the center horizontal crosshair. Estimating moving leads will require knowing yardage distance, wind speed, moving target speed, and total bullet flight times, including rifle lock time. Bullet flight times can be roughly calculated based on feet per second velocities or a ballistic calculator.

Note: Correctly estimating moving leads is very difficult and requires considerable practice and knowledge beyond the scope of this manual.



9.5 MOA reticle correction for a target moving 3 mph at a distance of 800 yards. No wind. Elevation already dialed into turret.



VIP WARRANTY™ OUR UNCONDITIONAL PROMISE TO YOU.

We promise to repair or replace the product. Absolutely free.

- ▶ Unlimited.
- ▶ Unconditional.
- ▶ Lifetime Warranty.

You do not have to register, save the box, or a receipt for the Warranty to be honored.

Learn more at VortexOptics.com

service@VortexOptics.com • 1-800-4VORTEX

Note: The VIP Warranty™ does not cover loss, theft, deliberate damage, or cosmetic damage not affecting product performance.

For the most up to date manual visit VortexOptics.com



M-00160-1

© 2022 Vortex Optics

® Registered Trademark and TM Trademark of Vortex Optics. Patent Pending